



SECTION A: ANNUAL SPECIFICATIONS

INSTRUCTIONS:

1. Items 1 through 8 and Section C are to be inspected annually.
2. For tilt measurements circle which side of the level the feeler gauges were placed under.
 - **7** For 7 pin side, **10** for 10 pin side, **P** for pin deck side, **F** for foul line side
3. **Copy page before inspection for centers with more than 8 lanes.**

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?		FAILING LANE NUMBERS
			Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
1	AUTOMATIC FOUL DEVICES	Light remains on for 10 to 15 seconds and triggers no more than 1/4" beyond of the approach side of the foul line.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
2	LANE PANEL DROP-OFFS	Drop off from trailing to leading edge. Specification: 0.000 – 0.040"	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
3	EDGE STRIPS	(FIBER OR SYNTHETIC) Specification: Edge strips must be intact with a smooth, curved edge.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
4	PIN SPOTTING	Specification: All pins must stand within their respective pin spots.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	

Pin Deck Type (Circle One) Wood or Synthetic If Synthetic: Manufacturer: _____ Model: _____

		Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	
		1	2	3	4	5	6	7	8	
5	Kickback Plate to Kickback Plate (at rear row of pins)	---	---	-	---	---	---	---	---	
	Spec Range: 59 5/8" 60"	59 3/4	59 3/4	59 3/4	59 5/8	59 3/4	59 3/4	59 3/4	59 5/8	
6	Crosswise Tilt of Pin Deck (at rear row of pins)	⁷ 0 ¹⁰	⁷ 0 ¹⁰	⁷ 0 ¹⁰	⁷ 20 ¹⁰	⁷ 0 ¹⁰	⁷ 35 ¹⁰	⁷ 20 ¹⁰	⁷ 0 ¹⁰	
	Spec Range: -0.040" 0.040"									
7	Lengthwise Tilt of Pin Deck	Between 4-7 pins	^F 130 ^P	^F 20 ^P	^F 90 ^P	^F 135 ^P	^F 120 ^P	^F 140 ^P	^F 130 ^P	^F 50 ^P
	Spec Range: -0.187" 0.187"	Between 6-10 pins	^F 130 ^P	^F 100 ^P	^F 90 ^P	^F 140 ^P	^F 125 ^P	^F 140 ^P	^F 130 ^P	^F 50 ^P
8	Gutter Depth (at rear row of pins)	7 pin side	3 5/8	3 5/8	3 5/8	3 5/8	3 5/8	3 5/8	3 1/2	3 5/8
	Spec Range: 3 3/8" 3 5/8"	10 pin side	3 5/8	3 5/8	3 5/8	3 5/8	3 5/8	3 5/8	3 5/8	3 5/8