



# SECTION A: ANNUAL SPECIFICATIONS

## INSTRUCTIONS:

- Items 1 through 8 and Section C are to be inspected annually.
- For tilt measurements circle which side of the level the feeler gauges were placed under.
  - **7** For 7 pin side, **10** for 10 pin side, **P** for pin deck side, **F** for foul line side
- Copy page before inspection for centers with more than 8 lanes.**

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?		FAILING LANE NUMBERS
			Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
1	AUTOMATIC FOUL DEVICES	Light remains on for 10 to 15 seconds and triggers no more than 1/4" beyond of the approach side of the foul line.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
2	LANE PANEL DROP-OFFS	Drop off from trailing to leading edge. Specification: 0.000 – 0.040"	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
3	EDGE STRIPS	(FIBER OR SYNTHETIC) Specification: Edge strips must be intact with a smooth, curved edge.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
4	PIN SPOTTING	Specification: All pins must stand within their respective pin spots.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	

**Pin Deck Type (Circle One) Wood or Synthetic If Synthetic: Manufacturer: \_\_\_\_\_ Model: \_\_\_\_\_**

				Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.
				9	10	-	-	-	-	-	-	-
5	Kickback Plate to Kickback Plate (at rear row of pins)			---	---	-	---	---	---	---	---	---
	Spec Range:	59 5/8"	60"	59 5/8	59 5/8							
6	Crosswise Tilt of Pin Deck (at rear row of pins)			7 10	7 10	7 10	7 10	7 10	7 10	7 10	7 10	7 10
	Spec Range:	-0.040"	0.040"	0	0							
7	Lengthwise Tilt of Pin Deck		Between 4-7 pins	F 110 P	F 130 P	F P	F P	F P	F P	F P	F P	F P
	Spec Range:	-0.187"	0.187"	Between 6-10 pins	F 130 P	F 135 P	F P	F P	F P	F P	F P	F P
8	Gutter Depth (at rear row of pins)		7 pin side	3 5/8	3 5/8							
	Spec Range:	3 3/8"	3 5/8"	10 pin side	3 1/2	3 1/2						