

A **Future** FOR
THE **Sport**



CANNON BALL LANES
2018

**CENTER
INSPECTION
REPORT**

It is recommended that a
Lane Dressing Inspection Report
be sent to USBC by September 15th.

USBC CENTER INSPECTION REPORT



CENTER INFORMATION

REPORT ANNUALLY

| | | | | | | |
|-------------------------------|--|--|-----------------------------------|---------------------------|-----------------|----------------|
| Certification Number: | 30179 | Center Name: | Cannon Ball Lanes | | Date: | 5/9/2018 |
| Association Number: | 82656 | Association Name: | Greater Fredericksburg USBC | | Business Phone: | (540) 295-9570 |
| Center Manager: | First: Megan | Last: | Sasser | | Business Phone: | (540) 653-7327 |
| Center Proprietor: | First: U.S. Navy | Last: | | | Business Phone: | |
| Center E-Mail Address: | | | | | | |
| Inspection Type: | Annual Inspection: <input checked="" type="checkbox"/> | New Installation: <input type="checkbox"/> | Overlay: <input type="checkbox"/> | | | |
| Total Lanes: | 10 | Number of Lanes Added: | 0 | Number of Lanes Replaced: | 0 | |
| Lanes to be Certified: | | | | | | |

REPORT WHEN DIFFERENT FROM PREVIOUS INSPECTION

| | | | | | | |
|--|------------------------------------|--------------------------------------|---|--------------------------------------|------------------------------------|---------------------------------------|
| Center Mailing Address: | Street: | City: | State: | Zip: | | |
| Center Physical Address: | Street: | City: | State: | Zip: | | |
| Proprietor's Mailing Address: | Street: | City: | State: | Zip: | | |
| Pinsetters: | Manufacturer: | | | | | |
| Lane Machine: | Yes: <input type="checkbox"/> | No: <input type="checkbox"/> | If yes: | Manufacturer: Model: | | |
| Pin Decks: | Wood: <input type="checkbox"/> | Synthetic: <input type="checkbox"/> | If synthetic: | Manufacturer: Model: | | |
| Lanes: | Wood: <input type="checkbox"/> | Synthetic: <input type="checkbox"/> | Multi-Surface: <input type="checkbox"/> | If synthetic: Manufacturer: Permit: | | |
| Resurfaced / Installed By: | Company: | | | Date resurfaced: | | |
| Resurfacers Stencil or Synthetic Model ID Appears On All Lanes: | Yes: <input type="checkbox"/> | No: <input type="checkbox"/> | | | | |
| Wood Lane Top Coat: | Urethane: <input type="checkbox"/> | Water Base: <input type="checkbox"/> | Epoxy: <input type="checkbox"/> | 100% Solid: <input type="checkbox"/> | Guardian: <input type="checkbox"/> | Lane Shield: <input type="checkbox"/> |

SECTION A: ANNUAL SPECIFICATIONS



INSTRUCTIONS:

- ITEMS 1 THROUGH 8 AND SECTION C ARE TO BE INSPECTED ANNUALLY.
- FOR TILT MEASUREMENTS CIRCLE WHICH SIDE OF THE LEVEL THE FEELER GAUGES WERE PLACED UNDER.
 - 7 FOR 7 PIN SIDE, 10 FOR 10 PIN SIDE, P FOR PIN DECK SIDE, F FOR FOUL LINE SIDE
- COPY PAGE BEFORE INSPECTION FOR CENTERS WITH MORE THAN 12 LANES.

NOTE: IT IS RECOMMENDED THAT A LANE DRESSING INSPECTION REPORT BE SENT TO USBC BY SEPTEMBER 15TH.

| ITEM | MEASUREMENT | DESCRIPTION | ALL LANES COMPLY? | | FAILING LANE NUMBERS |
|------|------------------------|--|--|---|----------------------|
| | | | Yes: <input type="checkbox"/> | No: <input type="checkbox"/> | |
| 1 | AUTOMATIC FOUL DEVICES | Light remains on for 10 to 15 seconds and triggers no more than ¼" beyond of the approach side of the foul line. | Yes: <input type="checkbox"/> | No: <input checked="" type="checkbox"/> | 5 & 6 |
| 2 | LANE PANEL DROP-OFFS | Drop off from trailing to leading edge. Specification: 0.000 – 0.040" | Yes: <input checked="" type="checkbox"/> | No: <input type="checkbox"/> | |
| 3 | EDGE STRIPS | (FIBRE OR SYNTHETIC) Specification: Edge strips must be intact with a smooth, curved edge. | Yes: <input checked="" type="checkbox"/> | No: <input type="checkbox"/> | |
| 4 | PIN SPOTTING | Specification: All pins must stand within their respective pin spots. | Yes: <input checked="" type="checkbox"/> | No: <input type="checkbox"/> | |

| | | | | Lane No. | Lane No. | Lane No. | Lane No. | Lane No. | Lane No. | Lane No. | Lane No. | Lane No. | Lane No. | Lane No. |
|---|---|---------|------------------|------------------------------------|-------------------------------------|------------------------------------|-------------------------------------|-------------------------------------|------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|------------------------------------|
| | | | | <u>1</u> | <u>2</u> | <u>3</u> | <u>4</u> | <u>5</u> | <u>6</u> | <u>7</u> | <u>8</u> | <u>9</u> | <u>10</u> | --- |
| 5 | Kickback Plate to Kickback Plate (at rear row of pins) | | | 59 5/8 | 59 3/4 | 59 3/4 | 59 3/4 | 59 3/4 | 59 7/8 | 59 3/4 | 59 3/4 | 59 5/8 | 59 3/4 | |
| | Spec Range: | 59 5/8" | 60" | | | | | | | | | | | |
| 6 | Crosswise Tilt (at rear row of pins) | | | ⁷ / ₁₀ 0 | ⁷ / ₁₀ 030 | ⁷ / ₁₀ 0 | ⁷ / ₁₀ 020 | ⁷ / ₁₀ 010 | ⁷ / ₁₀ 0 | ⁷ / ₁₀ 010 | ⁷ / ₁₀ 020 | ⁷ / ₁₀ 020 | ⁷ / ₁₀ 020 | ⁷ / ₁₀ |
| | Spec Range: | -0.040" | 0.040" | | | | | | | | | | | |
| 7 | Lengthwise Tilt | | Between 4-7 pins | ^F / _P 135 | ^F / _P 0 | ^F / _P 020 | ^F / _P 120 | ^F / _P 080 | ^F / _P 145 | ^F / _P 135 | ^F / _P 095 | ^F / _P 105 | ^F / _P 155 | ^F / _P |
| | Spec Range: | -0.187" | 0.187" | Between 6-10 pins | ^F / _P 135 | ^F / _P 090 | ^F / _P 040 | ^F / _P 120 | ^F / _P 145 | ^F / _P 135 | ^F / _P 135 | ^F / _P 095 | ^F / _P 135 | ^F / _P 170 |
| 8 | Gutter Depth (at rear row of pins) | | | 7 pin | 3 3/8 | 3 5/8 | 3 3/8 | 3 5/8 | 3 1/2 | 3 1/2 | 3 1/2 | 3 5/8 | 3 3/8 | |
| | Spec Range: | 3 3/8" | 3 5/8" | 10 pin | 3 1/2 | 3 5/8 | 3 3/8 | 3 1/2 | 3 5/8 | 3 5/8 | 3 1/2 | 3 1/2 | 3 5/8 | |

SYNTHETIC LANES



| ITEM | Crosswise Tilts, Crowns, & Depressions +/- 0.030" at installation +/- 0.040" annually | Lane No. | Lane No. | Lane No. | Lane No. | Lane No. | Lane No. | Lane No. | Lane No. | Lane No. | Lane No. | Lane No. | Lane No. | |
|-------------------------|---|------------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|--|
| | | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | --- | --- | |
| 20 Synthetic Panel 1 | Crosswise Tilt: | 20 | 0 | 30 | 40 | 40 | 0 | 20 | 0 | 20 | 20 | | | |
| | *Lengthwise Tilt: | F | | | | | | | | | | F | F | |
| | Crowns (+) & Depressions (-) | Right 10 board: | +27 | +35 | +20 | +20 | +40 | +20 | +40 | +40 | +23 | +12 | | |
| | | Center 20 board: | +20 | +32 | +14 | -16 | +40 | +20 | +30 | +35 | -10 | +22 | | |
| Distance: | 4 ft | Left 10 board: | +18 | -34 | -10 | +20 | -34 | -32 | -39 | +37 | +29 | +22 | | |
| 21 Synthetic Panel 2 | Crosswise Tilt: | 0 | 10 | 0 | 0 | 0 | 0 | 0 | 0 | 20 | 20 | | | |
| | *Lengthwise Tilt: | F | | | | | | | | | | F | F | |
| | Crowns (+) & Depressions (-) | Right 10 board: | +12 | +15 | -7 | -5 | -2 | 0 | -12 | +8 | +2 | -7 | | |
| | | Center 20 board: | +7 | +2 | -10 | +5 | -12 | +25 | +27 | +6 | +3 | +15 | | |
| Distance: | 16 ft | Left 10 board: | +19 | +15 | -3 | +10 | -7 | +3 | +20 | +8 | +7 | +8 | | |
| 22 Synthetic Panel 3 | Crosswise Tilt: | 20 | 10 | 0 | 20 | 0 | 0 | 20 | 20 | 30 | 20 | | | |
| | *Lengthwise Tilt: | F | | | | | | | | | | F | F | |
| | Crowns (+) & Depressions (-) | Right 10 board: | +5 | +15 | -12 | +15 | -10 | +18 | -7 | +12 | +10 | -3 | | |
| | | Center 20 board: | +3 | +2 | -3 | +2 | +5 | -7 | -2 | +15 | +7 | +17 | | |
| Distance: | 28 ft | Left 10 board: | -14 | +15 | -23 | +8 | +5 | +17 | +17 | +24 | +9 | 0 | | |
| 23 Synthetic Panel 4 | Crosswise Tilt: | 0 | 30 | 0 | 0 | 0 | 20 | 0 | 0 | 20 | 20 | | | |
| | *Lengthwise Tilt: | F | | | | | | | | | | F | F | |
| | Crowns (+) & Depressions (-) | Right 10 board: | +20 | +20 | -1 | +8 | -20 | +2 | +13 | +10 | -10 | -1 | | |
| | | Center 20 board: | +5 | -8 | -9 | -3 | -15 | +24 | -10 | +13 | -20 | +13 | | |
| Distance: | 40 ft | Left 10 board: | +21 | +22 | +5 | +18 | -20 | -7 | -12 | +22 | +7 | +2 | | |
| 24 Synthetic Panel 5 | Crosswise Tilt: | 0 | 0 | 0 | 20 | 0 | 0 | 0 | 0 | 30 | 10 | | | |
| | *Lengthwise Tilt: | F | | | | | | | | | | F | F | |
| | Crowns (+) & Depressions (-) | Right 15 board: | +8 | +25 | 0 | +20 | +14 | +10 | +10 | +12 | +40 | +22 | | |
| | | Left 15 board: | +11 | +27 | -13 | +19 | +8 | +12 | +13 | 0 | +12 | +22 | | |
| Distance: | 52 ft | | | | | | | | | | | | | |

Completed copies are to be given to:

- Local Association Manager
(must be kept for 2 years)
- Center Representative
- USBC Headquarters

E-mail:
certifications@bowl.com

Mail:
USBC Headquarters
621 Six Flags Dr
Arlington, TX, 76011
ATTN: Center Inspection Coordinator

WITHIN 10 DAYS OF INSPECTION.

Upon submission, this center shall be placed on pending status. Once it has been verified this center meets USBC specifications, it will become certified for the current bowling season and a certificate will be delivered to the center's mailing address on record. Should an additional inspection be required, see Center Re-Inspection Report on BOWL.com.

REPORT AUTHORIZATION

We, the undersigned, representing the listed bowling association, have measured and inspected the physical specifications of the lanes referred to in this report and certify the measurements listed herein to be accurate.

Lead Inspector: Print: Donnell Johnson Sign: _____ Date: _____

Association Manager: Print: Courtney Tripp Sign: _____ Date: _____

I hereby acknowledge receipt of this report, and apply for USBC Center Certification.

Center Representative: Print: Megan Sasser Sign: _____ Date: _____