

# SECTION A: ANNUAL SPECIFICATIONS



## INSTRUCTIONS:

- ITEMS 1 THROUGH 8 AND SECTION C ARE TO BE INSPECTED ANNUALLY.
- FOR TILT MEASUREMENTS CIRCLE WHICH SIDE OF THE LEVEL THE FEELER GAUGES WERE PLACED UNDER.
  - 7 FOR 7 PIN SIDE, 10 FOR 10 PIN SIDE, P FOR PIN DECK SIDE, F FOR FOUL LINE SIDE
- COPY PAGE BEFORE INSPECTION FOR CENTERS WITH MORE THAN 12 LANES.

**NOTE: IT IS RECOMMENDED THAT A LANE DRESSING INSPECTION REPORT BE SENT TO USBC BY SEPTEMBER 15TH.**

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?		FAILING LANE NUMBERS
			Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
1	AUTOMATIC FOUL DEVICES	Light remains on for 10 to 15 seconds and triggers no more than ¼" beyond of the approach side of the foul line.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
2	LANE PANEL DROP-OFFS	Drop off from trailing to leading edge. Specification: 0.000 – 0.040"	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
3	EDGE STRIPS	(FIBRE OR SYNTHETIC) Specification: Edge strips must be intact with a smooth, curved edge.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
4	PIN SPOTTING	Specification: All pins must stand within their respective pin spots.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	

				Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.		
				<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>5</u>	<u>6</u>	<u>7</u>	<u>8</u>	<u>9</u>	<u>10</u>	<u>11</u>	<u>12</u>	
5	Kickback Plate to Kickback Plate (at rear row of pins)			59 11/16	59 13/16	59 11/16	59 3/4	59 11/16	59 5/8	59 3/4	59 3/4	59 11/16	59 11/16	59 3/4	59 13/16	
	Spec Range:	59 5/8"	60"													
6	Crosswise Tilt (at rear row of pins)			<sup>7</sup> / <sub>10</sub> 0	<sup>7</sup> / <sub>10</sub> 0	<sup>7</sup> / <sub>10</sub> <b>0</b>	<sup>7</sup> / <sub>10</sub> 0	<sup>7</sup> / <sub>10</sub> <b>010</b>	<sup>7</sup> / <sub>10</sub> <b>040</b>	<sup>7</sup> / <sub>10</sub> 0	<sup>7</sup> / <sub>10</sub> 0	<sup>7</sup> / <sub>10</sub> <b>030</b>	<sup>7</sup> / <sub>10</sub> 0	<sup>7</sup> / <sub>10</sub> 0	<sup>7</sup> / <sub>10</sub> 0	
	Spec Range:	-0.040"	0.040"													
7	Lengthwise Tilt		Between 4-7 pins	<sup>F</sup> / <sub>P</sub> <b>030</b>	<sup>F</sup> / <sub>P</sub> <b>045</b>	<sup>F</sup> / <sub>P</sub> <b>050</b>	<sup>F</sup> / <sub>P</sub> 0	<sup>F</sup> / <sub>P</sub> <b>040</b>	<sup>F</sup> / <sub>P</sub> 115	<sup>F</sup> / <sub>P</sub> <b>010</b>	<sup>F</sup> / <sub>P</sub> 080	<sup>F</sup> / <sub>P</sub> <b>095</b>	<sup>F</sup> / <sub>P</sub> <b>030</b>	<sup>F</sup> / <sub>P</sub> <b>050</b>	<sup>F</sup> / <sub>P</sub> <b>005</b>	
	Spec Range:	-0.187"	0.187"	Between 6-10 pins	<sup>F</sup> / <sub>P</sub> <b>040</b>	<sup>F</sup> / <sub>P</sub> 0	<sup>F</sup> / <sub>P</sub> <b>020</b>	<sup>F</sup> / <sub>P</sub> 015	<sup>F</sup> / <sub>P</sub> 0	<sup>F</sup> / <sub>P</sub> 115	<sup>F</sup> / <sub>P</sub> <b>005</b>	<sup>F</sup> / <sub>P</sub> 090	<sup>F</sup> / <sub>P</sub> <b>105</b>	<sup>F</sup> / <sub>P</sub> <b>050</b>	<sup>F</sup> / <sub>P</sub> <b>030</b>	<sup>F</sup> / <sub>P</sub> <b>010</b>
8	Gutter Depth (at rear row of pins)			7 pin	3 5/8	3 1/2	3 1/2	3 3/8	3 1/2	3 5/8	3 5/8	3 5/8	3 1/2	3 3/8	3 1/2	3 5/8
	Spec Range:	3 3/8"	3 5/8"	10 pin	3 1/2	3 1/2	3 1/2	3 1/2	3 5/8	3 5/8	3 5/8	3 5/8	3 5/8	3 1/2	3 5/8	3 5/8