

# SECTION A: ANNUAL SPECIFICATIONS



## INSTRUCTIONS:

- ITEMS 1 THROUGH 8 AND SECTION C ARE TO BE INSPECTED ANNUALLY.
- FOR TILT MEASUREMENTS CIRCLE WHICH SIDE OF THE LEVEL THE FEELER GAUGES WERE PLACED UNDER.
  - 7 FOR 7 PIN SIDE, 10 FOR 10 PIN SIDE, P FOR PIN DECK SIDE, F FOR FOUL LINE SIDE
- COPY PAGE BEFORE INSPECTION FOR CENTERS WITH MORE THAN 12 LANES.

**NOTE: IT IS RECOMMENDED THAT A LANE DRESSING INSPECTION REPORT BE SENT TO USBC BY SEPTEMBER 15TH.**

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?		FAILING LANE NUMBERS
			Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
1	AUTOMATIC FOUL DEVICES	Light remains on for 10 to 15 seconds and triggers no more than ¼" beyond of the approach side of the foul line.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
2	LANE PANEL DROP-OFFS	Drop off from trailing to leading edge. Specification: 0.000 – 0.040"	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
3	EDGE STRIPS	(FIBRE OR SYNTHETIC) Specification: Edge strips must be intact with a smooth, curved edge.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
4	PIN SPOTTING	Specification: All pins must stand within their respective pin spots.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	

				Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	
				13	14	15	16	17	18	19	20	21	22	23	24
5	Kickback Plate to Kickback Plate (at rear row of pins)			59 11/16	59 15/16	59 5/8	59 11/16	59 3/4	59 11/16	59 5/8	59 13/16	59 3/4	59 5/8	59 5/8	59 7/8
	Spec Range:	59 5/8"	60"												
6	Crosswise Tilt (at rear row of pins)			<sup>7</sup> / <sub>10</sub> 0	<sup>7</sup> / <sub>10</sub> 040	<sup>7</sup> / <sub>10</sub> 040	<sup>7</sup> / <sub>10</sub> 040	<sup>7</sup> / <sub>10</sub> 020	<sup>7</sup> / <sub>10</sub> 030	<sup>7</sup> / <sub>10</sub> 020	<sup>7</sup> / <sub>10</sub> 020	<sup>7</sup> / <sub>10</sub> 020	<sup>7</sup> / <sub>10</sub> 0	<sup>7</sup> / <sub>10</sub> 020	<sup>7</sup> / <sub>10</sub> 020
	Spec Range:	-0.040"	0.040"												
7	Lengthwise Tilt		Between 4-7 pins	<sup>F</sup> / <sub>P</sub> 010	<sup>F</sup> / <sub>P</sub> 090	<sup>F</sup> / <sub>P</sub> 040	<sup>F</sup> / <sub>P</sub> 040	<sup>F</sup> / <sub>P</sub> 040	<sup>F</sup> / <sub>P</sub> 030	<sup>F</sup> / <sub>P</sub> 020	<sup>F</sup> / <sub>P</sub> 040	<sup>F</sup> / <sub>P</sub> 070	<sup>F</sup> / <sub>P</sub> 080	<sup>F</sup> / <sub>P</sub> 030	<sup>F</sup> / <sub>P</sub> 030
	Spec Range:	-0.187"	0.187"	Between 6-10 pins	<sup>F</sup> / <sub>P</sub> 010	<sup>F</sup> / <sub>P</sub> 070	<sup>F</sup> / <sub>P</sub> 040	<sup>F</sup> / <sub>P</sub> 040	<sup>F</sup> / <sub>P</sub> 040	<sup>F</sup> / <sub>P</sub> 040	<sup>F</sup> / <sub>P</sub> 050	<sup>F</sup> / <sub>P</sub> 040	<sup>F</sup> / <sub>P</sub> 060	<sup>F</sup> / <sub>P</sub> 100	<sup>F</sup> / <sub>P</sub> 030
8	Gutter Depth (at rear row of pins)			7 pin	3 3/8	3 1/2	3 5/8	3 5/8	3 1/2	3 5/8	3 3/8	3 1/2	3 3/8	3 1/2	3 1/2
	Spec Range:	3 3/8"	3 5/8"	10 pin	3 1/2	3 5/8	3 3/8	3 3/8	3 1/2	3 1/2	3 3/8	3 3/8	3 1/2	3 1/2	3 3/8