

A **Future** FOR
THE **Sport**

AMF FREDERICKSBURG
2018

**CENTER
INSPECTION
REPORT**

It is recommended that a
Lane Dressing Inspection Report
be sent to USBC by September 15th.

USBC CENTER INSPECTION REPORT



CENTER INFORMATION

REPORT ANNUALLY

Certification Number:	20001	Center Name:	AMF Fredericksburg	Date:	6/20/2018
Association Number:	82656	Association Name:	Greater Fredericksburg USBC	Business Phone:	(540) 295-9570
Center Manager:	First:	Last:		Business Phone:	(540) 786-2695
Center Proprietor:	First:	Last:		Business Phone:	
Center E-Mail Address:					
Inspection Type:	Annual Inspection: <input checked="" type="checkbox"/>	New Installation: <input type="checkbox"/>	Overlay: <input type="checkbox"/>		
Total Lanes:	50	Number of Lanes Added:	0	Number of Lanes Replaced:	0
Lanes to be Certified:					

REPORT WHEN DIFFERENT FROM PREVIOUS INSPECTION

Center Mailing Address:	Street:	City:	State:	Zip:		
Center Physical Address:	Street:	City:	State:	Zip:		
Proprietor's Mailing Address:	Street:	City:	State:	Zip:		
Pinsetters:	Manufacturer:					
Lane Machine:	Yes: <input type="checkbox"/>	No: <input type="checkbox"/>	If yes:	Manufacturer: Model:		
Pin Decks:	Wood: <input type="checkbox"/>	Synthetic: <input type="checkbox"/>	If synthetic:	Manufacturer: Model:		
Lanes:	Wood: <input type="checkbox"/>	Synthetic: <input type="checkbox"/>	Multi-Surface: <input type="checkbox"/>	If synthetic: Manufacturer: Permit:		
Resurfaced / Installed By:	Company:			Date resurfaced:		
Resurfacers Stencil or Synthetic Model ID Appears On All Lanes:	Yes: <input type="checkbox"/>	No: <input type="checkbox"/>				
Wood Lane Top Coat:	Urethane: <input type="checkbox"/>	Water Base: <input type="checkbox"/>	Epoxy: <input type="checkbox"/>	100% Solid: <input type="checkbox"/>	Guardian: <input type="checkbox"/>	Lane Shield: <input type="checkbox"/>

SECTION A: ANNUAL SPECIFICATIONS



INSTRUCTIONS:

- ITEMS 1 THROUGH 8 AND SECTION C ARE TO BE INSPECTED ANNUALLY.
- FOR TILT MEASUREMENTS CIRCLE WHICH SIDE OF THE LEVEL THE FEELER GAUGES WERE PLACED UNDER.
 - 7 FOR 7 PIN SIDE, 10 FOR 10 PIN SIDE, P FOR PIN DECK SIDE, F FOR FOUL LINE SIDE
- COPY PAGE BEFORE INSPECTION FOR CENTERS WITH MORE THAN 12 LANES.

NOTE: IT IS RECOMMENDED THAT A LANE DRESSING INSPECTION REPORT BE SENT TO USBC BY SEPTEMBER 15TH.

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?		FAILING LANE NUMBERS
			Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
1	AUTOMATIC FOUL DEVICES	Light remains on for 10 to 15 seconds and triggers no more than ¼" beyond of the approach side of the foul line.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
2	LANE PANEL DROP-OFFS	Drop off from trailing to leading edge. Specification: 0.000 – 0.040"	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
3	EDGE STRIPS	(FIBRE OR SYNTHETIC) Specification: Edge strips must be intact with a smooth, curved edge.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
4	PIN SPOTTING	Specification: All pins must stand within their respective pin spots.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	

				Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	
				<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>5</u>	<u>6</u>	<u>7</u>	<u>8</u>	<u>9</u>	<u>10</u>	<u>11</u>	<u>12</u>
5	Kickback Plate to Kickback Plate (at rear row of pins)			59 3/4	59 5/8	59 7/8	59 7/8	59 3/4	59 3/4	59 11/16	59 11/16	59 11/16	59 3/4	59 11/16	59 3/4
	Spec Range:	59 5/8"	60"												
6	Crosswise Tilt (at rear row of pins)			⁷ / ₁₀	⁷ / ₁₀	⁷ / ₁₀	⁷ / ₁₀	⁷ / ₁₀	⁷ / ₁₀	⁷ / ₁₀	⁷ / ₁₀	⁷ / ₁₀	⁷ / ₁₀	⁷ / ₁₀	⁷ / ₁₀
	Spec Range:	-0.040"	0.040"	0	020	0	020	0	020	020	020	040	020	0	020
7	Lengthwise Tilt		Between 4-7 pins	^F / _P	^F / _P	^F / _P	^F / _P	^F / _P	^F / _P	^F / _P	^F / _P	^F / _P	^F / _P	^F / _P	^F / _P
	Spec Range:	-0.187"	0.187"	040	020	0	020	030	020	0	120	0	085	030	040
8	Gutter Depth (at rear row of pins)			7 pin	3 1/2	3 1/2	3 5/8	3 1/2	3 1/2	3 3/8	3 5/8	3 3/8	3 1/2	3 5/8	3 5/8
	Spec Range:	3 3/8"	3 5/8"	10 pin	3 1/2	3 3/8	3 5/8	3 3/8	3 5/8	3 3/4	3 5/8	3 1/2	3 1/2	3 1/2	3 1/2

SECTION A: ANNUAL SPECIFICATIONS



INSTRUCTIONS:

- ITEMS 1 THROUGH 8 AND SECTION C ARE TO BE INSPECTED ANNUALLY.
- FOR TILT MEASUREMENTS CIRCLE WHICH SIDE OF THE LEVEL THE FEELER GAUGES WERE PLACED UNDER.
 - 7 FOR 7 PIN SIDE, 10 FOR 10 PIN SIDE, P FOR PIN DECK SIDE, F FOR FOUL LINE SIDE
- COPY PAGE BEFORE INSPECTION FOR CENTERS WITH MORE THAN 12 LANES.

NOTE: IT IS RECOMMENDED THAT A LANE DRESSING INSPECTION REPORT BE SENT TO USBC BY SEPTEMBER 15TH.

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?		FAILING LANE NUMBERS
			Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
1	AUTOMATIC FOUL DEVICES	Light remains on for 10 to 15 seconds and triggers no more than ¼" beyond of the approach side of the foul line.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
2	LANE PANEL DROP-OFFS	Drop off from trailing to leading edge. Specification: 0.000 – 0.040"	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
3	EDGE STRIPS	(FIBRE OR SYNTHETIC) Specification: Edge strips must be intact with a smooth, curved edge.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
4	PIN SPOTTING	Specification: All pins must stand within their respective pin spots.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	

				Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.		
				13	14	15	16	17	18	19	20	21	22	23	24	
5	Kickback Plate to Kickback Plate (at rear row of pins)			59 11/16	59 13/16	59 11/16	59 3/4	59 11/16	59 5/8	59 3/4	59 3/4	59 11/16	59 11/16	59 3/4	59 13/16	
	Spec Range:	59 5/8"	60"													
6	Crosswise Tilt (at rear row of pins)			⁷ / ₁₀ 0	⁷ / ₁₀ 0	⁷ / ₁₀ 020	⁷ / ₁₀ 0	⁷ / ₁₀ 010	⁷ / ₁₀ 040	⁷ / ₁₀ 0	⁷ / ₁₀ 0	⁷ / ₁₀ 030	⁷ / ₁₀ 0	⁷ / ₁₀ 0	⁷ / ₁₀ 0	
	Spec Range:	-0.040"	0.040"													
7	Lengthwise Tilt		Between 4-7 pins	^F / _P 030	^F / _P 045	^F / _P 050	^F / _P 0	^F / _P 040	^F / _P 115	^F / _P 010	^F / _P 080	^F / _P 095	^F / _P 030	^F / _P 050	^F / _P 005	
	Spec Range:	-0.187"	0.187"	Between 6-10 pins	^F / _P 040	^F / _P 0	^F / _P 020	^F / _P 015	^F / _P 0	^F / _P 115	^F / _P 005	^F / _P 090	^F / _P 105	^F / _P 050	^F / _P 030	^F / _P 010
8	Gutter Depth (at rear row of pins)			7 pin	3 5/8	3 1/2	3 1/2	3 3/8	3 1/2	3 5/8	3 5/8	3 5/8	3 1/2	3 3/8	3 1/2	3 5/8
	Spec Range:	3 3/8"	3 5/8"	10 pin	3 1/2	3 1/2	3 1/2	3 1/2	3 5/8	3 5/8	3 5/8	3 5/8	3 5/8	3 1/2	3 5/8	3 5/8

SECTION A: ANNUAL SPECIFICATIONS



INSTRUCTIONS:

- ITEMS 1 THROUGH 8 AND SECTION C ARE TO BE INSPECTED ANNUALLY.
- FOR TILT MEASUREMENTS CIRCLE WHICH SIDE OF THE LEVEL THE FEELER GAUGES WERE PLACED UNDER.
 - 7 FOR 7 PIN SIDE, 10 FOR 10 PIN SIDE, P FOR PIN DECK SIDE, F FOR FOUL LINE SIDE
- COPY PAGE BEFORE INSPECTION FOR CENTERS WITH MORE THAN 12 LANES.

NOTE: IT IS RECOMMENDED THAT A LANE DRESSING INSPECTION REPORT BE SENT TO USBC BY SEPTEMBER 15TH.

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?		FAILING LANE NUMBERS
			Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
1	AUTOMATIC FOUL DEVICES	Light remains on for 10 to 15 seconds and triggers no more than ¼" beyond of the approach side of the foul line.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
2	LANE PANEL DROP-OFFS	Drop off from trailing to leading edge. Specification: 0.000 – 0.040"	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
3	EDGE STRIPS	(FIBRE OR SYNTHETIC) Specification: Edge strips must be intact with a smooth, curved edge.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
4	PIN SPOTTING	Specification: All pins must stand within their respective pin spots.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	

				Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	
				25	26	27	28	29	30	31	32	33	34	35	36
5	Kickback Plate to Kickback Plate (at rear row of pins)			59 11/16	59 7/8	59 3/4	59 5/8	59 5/8	59 13/16	59 5/8	59 5/8	59 11/16	59 5/8	59 5/8	59 5/8
	Spec Range:	59 5/8"	60"												
6	Crosswise Tilt (at rear row of pins)			⁷ / ₁₀ 0	⁷ / ₁₀ 020	⁷ / ₁₀ 015	⁷ / ₁₀ 040	⁷ / ₁₀ 0	⁷ / ₁₀ 040	⁷ / ₁₀ 020	⁷ / ₁₀ 010	⁷ / ₁₀ 020	⁷ / ₁₀ 0	⁷ / ₁₀ 020	⁷ / ₁₀ 0
	Spec Range:	-0.040"	0.040"												
7	Lengthwise Tilt		Between 4-7 pins	^F / _P 030	^F / _P 080	^F / _P 105	^F / _P 060	^F / _P 050	^F / _P 080	^F / _P 095	^F / _P 030	^F / _P 040	^F / _P 040	^F / _P 040	^F / _P 080
	Spec Range:	-0.187"	0.187"	Between 6-10 pins	^F / _P 020	^F / _P 060	^F / _P 115	^F / _P 060	^F / _P 040	^F / _P 080	^F / _P 095	^F / _P 020	^F / _P 040	^F / _P 040	^F / _P 060
8	Gutter Depth (at rear row of pins)			7 pin	3 1/2	3 3/8	3 1/2	3 5/8	3 5/8	3 1/2	3 3/8	3 1/2	3 1/2	3 1/2	3 1/2
	Spec Range:	3 3/8"	3 5/8"	10 pin	3 3/8	3 3/8	3 1/2	3 5/8	3 5/8	3 5/8	3 3/8	3 1/2	3 3/8	3 1/2	3 3/8

SECTION A: ANNUAL SPECIFICATIONS



INSTRUCTIONS:

- ITEMS 1 THROUGH 8 AND SECTION C ARE TO BE INSPECTED ANNUALLY.
- FOR TILT MEASUREMENTS CIRCLE WHICH SIDE OF THE LEVEL THE FEELER GAUGES WERE PLACED UNDER.
 - 7 FOR 7 PIN SIDE, 10 FOR 10 PIN SIDE, P FOR PIN DECK SIDE, F FOR FOUL LINE SIDE
- COPY PAGE BEFORE INSPECTION FOR CENTERS WITH MORE THAN 12 LANES.

NOTE: IT IS RECOMMENDED THAT A LANE DRESSING INSPECTION REPORT BE SENT TO USBC BY SEPTEMBER 15TH.

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?		FAILING LANE NUMBERS
			Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
1	AUTOMATIC FOUL DEVICES	Light remains on for 10 to 15 seconds and triggers no more than ¼" beyond of the approach side of the foul line.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
2	LANE PANEL DROP-OFFS	Drop off from trailing to leading edge. Specification: 0.000 – 0.040"	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
3	EDGE STRIPS	(FIBRE OR SYNTHETIC) Specification: Edge strips must be intact with a smooth, curved edge.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
4	PIN SPOTTING	Specification: All pins must stand within their respective pin spots.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	

				Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.		
				37	38	39	40	41	42	43	44	45	46	47	48	
5	Kickback Plate to Kickback Plate (at rear row of pins)			59 3/4	59 7/8	59 3/4	59 3/4	59 3/4	59 3/4	59 3/4	59 7/8	59 3/4	59 3/4	59 3/4	59 3/4	
	Spec Range:	59 5/8"	60"													
6	Crosswise Tilt (at rear row of pins)			7 10 0	7 10 020	7 10 020	7 10 0	7 10 020	7 10 020	7 10 020	7 10 020	7 10 0	7 10 040	7 10 020	7 10 040	
	Spec Range:	-0.040"	0.040"													
7	Lengthwise Tilt		Between 4-7 pins	F P 060	F P 040	F P 060	F P 050	F P 070	F P 100	F P 060	F P 020	F P 060	F P 020	F P 040	F P 100	
	Spec Range:	-0.187"	0.187"	Between 6-10 pins	F P 060	F P 060	F P 060	F P 050	F P 100	F P 100	F P 060	F P 040	F P 080	F P 020	F P 0	F P 100
8	Gutter Depth (at rear row of pins)			7 pin	3 3/8	3 3/8	3 3/8	3 3/8	3 3/8	3 3/8	3 1/2	3 1/2	3 3/8	3 1/2	3 1/2	3 3/8
	Spec Range:	3 3/8"	3 5/8"	10 pin	3 1/2	3 1/2	3 3/8	3 3/8	3 3/8	3 3/8	3 3/8	3 1/2	3 3/8	3 1/2	3 3/8	3 1/2

SECTION A: ANNUAL SPECIFICATIONS



INSTRUCTIONS:

- ITEMS 1 THROUGH 8 AND SECTION C ARE TO BE INSPECTED ANNUALLY.
- FOR TILT MEASUREMENTS CIRCLE WHICH SIDE OF THE LEVEL THE FEELER GAUGES WERE PLACED UNDER.
 - 7 FOR 7 PIN SIDE, 10 FOR 10 PIN SIDE, P FOR PIN DECK SIDE, F FOR FOUL LINE SIDE
- COPY PAGE BEFORE INSPECTION FOR CENTERS WITH MORE THAN 12 LANES.

NOTE: IT IS RECOMMENDED THAT A LANE DRESSING INSPECTION REPORT BE SENT TO USBC BY SEPTEMBER 15TH.

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?		FAILING LANE NUMBERS
1	AUTOMATIC FOUL DEVICES	Light remains on for 10 to 15 seconds and triggers no more than ¼" beyond of the approach side of the foul line.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
2	LANE PANEL DROP-OFFS	Drop off from trailing to leading edge. Specification: 0.000 – 0.040"	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
3	EDGE STRIPS	(FIBRE OR SYNTHETIC) Specification: Edge strips must be intact with a smooth, curved edge.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
4	PIN SPOTTING	Specification: All pins must stand within their respective pin spots.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	

			Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.
			49	50	---	---	---	---	---	---	---	---	---
5	Kickback Plate to Kickback Plate (at rear row of pins)		59 3/4	59 3/4									
	Spec Range:	59 5/8" 60"											
6	Crosswise Tilt (at rear row of pins)		7 10 20	7 10 0	7 10	7 10	7 10	7 10	7 10	7 10	7 10	7 10	7 10
	Spec Range:	-0.040" 0.040"											
7	Lengthwise Tilt		Between 4-7 pins	P 030	P 040	F P	F P	F P	F P	F P	F P	F P	F P
	Spec Range:	-0.187" 0.187"	Between 6-10 pins	P 040	P 050	F P	F P	F P	F P	F P	F P	F P	F P
8	Gutter Depth (at rear row of pins)		7 pin	3 3/8	3 3/8								
	Spec Range:	3 3/8" 3 5/8"	10 pin	3 3/8	3 3/8								

SYNTHETIC LANES

ITEM	Crosswise Tilts, Crowns, & Depressions +/- 0.030" at installation +/- 0.040" annually	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	
		<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>5</u>	<u>6</u>	<u>7</u>	<u>8</u>	<u>9</u>	<u>10</u>	<u>11</u>	<u>12</u>	
20 Synthetic Panel 1	Crosswise Tilt:	$\frac{7}{10}$ 0	$\frac{7}{10}$ 05	$\frac{7}{10}$ 0	$\frac{7}{10}$ 40	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 10	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	-10	-12	-3	+1	-10	-22	-38	-11	-15	+6	+8	+10
		Center 20 board:	-20	-12	-3	+1	-10	-22	-40	-17	-19	-1	-1	+5
Distance:	4 ft	Left 10 board:	-18	-8	-2	+3	-11	-17	-25	+4	-19	+18	-10	+5
21 Synthetic Panel 2	Crosswise Tilt:	$\frac{7}{10}$ 15	$\frac{7}{10}$ 10	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 20	$\frac{7}{10}$ 20	$\frac{7}{10}$ 40	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	-13	-5	-4	-9	-3	-8	+8	-6	+13	+2	-13	-23
		Center 20 board:	-8	-28	-9	-5	-2	-6	-8	+14	+13	-4	-14	-28
Distance:	16 ft	Left 10 board:	0	-3	+10	+6	-5	-3	+21	+3	+17	+2	-1	-18
22 Synthetic Panel 3	Crosswise Tilt:	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 10	$\frac{7}{10}$ 40	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	-4	-24	-16	-18	-16	-12	+8	-5	-20	-1	-26	-9
		Center 20 board:	-1	-26	-15	-17	-13	-4	+8	+2	-18	+4	-30	-10
Distance:	28 ft	Left 10 board:	+2	-11	0	-4	-7	-3	+5	+3	-10	+4	-17	-6
23 Synthetic Panel 4	Crosswise Tilt:	$\frac{7}{10}$ 10	$\frac{7}{10}$ 10	$\frac{7}{10}$ 10	$\frac{7}{10}$ 20	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 10	$\frac{7}{10}$ 40	$\frac{7}{10}$ 20	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	-20	-9	-7	+6	+12	-4	-2	-1	-20	-2	+2	+11
		Center 20 board:	-24	-16	-8	+10	+11	-9	-2	-1	-25	-3	0	+15
Distance:	40 ft	Left 10 board:	-11	-6	+2	+11	+4	-10	+5	+3	-8	+2	+4	+11
24 Synthetic Panel 5	Crosswise Tilt:	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 10	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 20	$\frac{7}{10}$ 20	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 15 board:	-8	-8	-6	+6	-12	-8	-3	+9	+13	+7	-4	-20
Left 15 board:		-6	-5	-5	0	-13	-11	-1	+8	+15	+6	-3	-20	
Distance:	52 ft													

SYNTHETIC LANES

ITEM	Crosswise Tilts, Crowns, & Depressions +/- 0.030" at installation +/- 0.040" annually	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	
		13	14	15	16	17	18	19	20	21	22	23	24	
20 Synthetic Panel 1	Crosswise Tilt:	$\frac{7}{10}$ 40	$\frac{7}{10}$ 20	$\frac{7}{10}$ 20	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 10	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 20	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	+1	-1	-18	-1	-11	+10	-17	-29	+11	+15	-17	-17
		Center 20 board:	-2	+4	-22	-2	-4	+13	-34	-34	+3	+3	-22	-34
Distance: 4 ft		Left 10 board:	+5	-5	-20	+4	-8	+20	-13	-15	+5	+4	-9	-10
21 Synthetic Panel 2	Crosswise Tilt:	$\frac{7}{10}$ 20	$\frac{7}{10}$ 20	$\frac{7}{10}$ 20	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 10	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	+3	+1	-18	-20	+1	-13	-13	+8	-11	-8	-4	0
		Center 20 board:	-18	+5	-20	-26	+15	-14	-28	+7	-21	0	-13	-12
Distance: 16 ft		Left 10 board:	-3	-3	-14	-30	+11	-9	-9	+20	-17	+5	+6	-4
22 Synthetic Panel 3	Crosswise Tilt:	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 40	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	+4	-10	+3	-18	-1	-16	-4	-2	-9	-8	-1	-8
		Center 20 board:	+6	-7	+6	-17	-1	-23	+1	-1	-5	-3	0	-2
Distance: 28 ft		Left 10 board:	+6	0	-8	-11	+8	-18	-3	0	-1	+3	0	-1
23 Synthetic Panel 4	Crosswise Tilt:	$\frac{7}{10}$ 10	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 10	$\frac{7}{10}$ 10	$\frac{7}{10}$ 10	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	+11	+38	-2	-10	+25	+13	-3	+4	-8	-23	+4	+5
		Center 20 board:	+15	+34	+1	-3	+28	+13	0	+4	-11	-30	+5	+6
Distance: 40 ft		Left 10 board:	+14	+30	+5	-5	-29	+11	+2	+3	-8	-21	+10	+9
24 Synthetic Panel 5	Crosswise Tilt:	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 15 board:	-12	-10	-7	-19	+1	-4	-6	-11	-3	-13	+11	-7
		Left 15 board:	-15	-8	-8	-23	-4	-4	-6	-10	-2	+11	+17	-5
Distance: 52 ft														

SYNTHETIC LANES



ITEM	Crosswise Tilts, Crowns, & Depressions +/- 0.030" at installation +/- 0.040" annually	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	
		25	26	27	28	29	30	31	32	33	34	35	36	
20 Synthetic Panel 1	Crosswise Tilt:	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	-18	-4	0	-24	-4	-2	+14	-10	-28	-3	-8	+10
		Center 20 board:	-25	-10	-10	-34	-15	-18	-4	-11	-29	-26	-8	+11
Distance: 4 ft		Left 10 board:	-17	-6	-8	-19	-6	+2	+9	-11	-15	-8	-5	+9
21 Synthetic Panel 2	Crosswise Tilt:	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 10	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	-4	-2	-24	+10	+18	+10	-9	+17	+10	+5	+10	+13
		Center 20 board:	-24	-27	-35	-8	-5	-10	-29	0	-15	-18	0	-8
Distance: 16 ft		Left 10 board:	-20	+7	-19	+10	+5	-16	-12	+10	+5	+6	+10	+22
22 Synthetic Panel 3	Crosswise Tilt:	$\frac{7}{10}$ 10	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 40	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	-14	+1	-3	-1	-17	-12	-5	-4	-6	-29	-22	+2
		Center 20 board:	-15	+5	-1	0	-20	-11	0	+3	-4	-40	-13	-4
Distance: 28 ft		Left 10 board:	-12	+6	+1	+4	-14	-9	+5	+5	-2	-34	-15	-8
23 Synthetic Panel 4	Crosswise Tilt:	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 10	$\frac{7}{10}$ 0	$\frac{7}{10}$ 10	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	-7	0	-11	-8	+5	-8	+3	-2	+11	-1	-2	-10
		Center 20 board:	-11	-2	-21	-10	+9	-10	+3	-4	+15	+8	-8	-8
Distance: 40 ft		Left 10 board:	-6	+4	-18	-7	+6	-7	+6	-4	+12	+10	-9	-1
24 Synthetic Panel 5	Crosswise Tilt:	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 10	$\frac{7}{10}$ 0	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 0	$\frac{7}{10}$ 20	$\frac{7}{10}$ 10	$\frac{7}{10}$ 0	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 15 board:	-18	-4	-7	+3	-16	-10	+20	-24	-6	0	-22	-12
		Left 15 board:	-19	-1	-9	0	-17	-10	+16	-22	-5	+7	-17	-2
Distance: 52 ft														

SYNTHETIC LANES



ITEM	Crosswise Tilts, Crowns, & Depressions +/- 0.030" at installation +/- 0.040" annually	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	
		37	38	39	40	41	42	43	44	45	46	47	48	
20 Synthetic Panel 1	Crosswise Tilt:	7/10 20	7/10 0	7/10 20	7/10 20	7/10 30	7/10 10	7/10 20	7/10 10	7/10 20	7/10 0	7/10 0	7/10 10	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	-8	-4	+7	-7	0	+2	+12	-10	-5	+7	-13	-6
		Center 20 board:	-5	-10	+5	-6	-18	+2	+1	-8	-7	+12	-18	-5
Distance: 4 ft		Left 10 board:	+13	-15	+6	0	-13	0	-5	0	-11	+10	-11	-4
21 Synthetic Panel 2	Crosswise Tilt:	7/10 0	7/10 0	7/10 0	7/10 20	7/10 0	7/10 0	7/10 0	7/10 0	7/10 0	7/10 0	7/10 20	7/10 0	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	+32	+20	+5	+11	-10	-20	-2	-11	+3	-4	-34	-1
		Center 20 board:	+38	+22	+2	+18	-18	-35	-8	-25	-10	-7	+22	-4
Distance: 16 ft		Left 10 board:	+16	+28	+23	+20	-1	0	+2	-18	+5	+1	+22	-6
22 Synthetic Panel 3	Crosswise Tilt:	7/10 40	7/10 20	7/10 0	7/10 0	7/10 0	7/10 0	7/10 20	7/10 0	7/10 0	7/10 0	7/10 0	7/10 0	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	+15	+10	+15	-19	+30	-1	+1	+9	-2	+10	-6	-9
		Center 20 board:	+15	+2	+13	-24	+31	+4	+3	+9	-16	+13	-4	-12
Distance: 28 ft		Left 10 board:	+10	0	+12	-20	+26	+2	+8	0	-5	+16	+1	-18
23 Synthetic Panel 4	Crosswise Tilt:	7/10 20	7/10 20	7/10 20	7/10 20	7/10 20	7/10 0	7/10 0	7/10 0	7/10 20	7/10 0	7/10 0	7/10 0	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 10 board:	-14	+22	+6	-5	+20	-2	+8	-6	+4	-12	0	-6
		Center 20 board:	-13	+18	+3	-9	+20	+11	+10	-5	+2	-16	-4	-4
Distance: 40 ft		Left 10 board:	-3	+10	+5	0	+5	+10	+14	-5	+3	-2	+1	-4
24 Synthetic Panel 5	Crosswise Tilt:	7/10 10	7/10 20	7/10 0	7/10 0	7/10 20	7/10 0	7/10 0	7/10 0	7/10 20	7/10 20	7/10 0	7/10 0	
	*Lengthwise Tilt:	F	F	F	F	F	F	F	F	F	F	F	F	
	Crowns (+) & Depressions (-)	Right 15 board:	+35	+22	+10	-1	+9	+15	+15	+5	+20	-1	+5	+9
		Left 15 board:	+38	+20	+8	+8	+8	+10	+8	0	+12	-8	+12	+5
Distance: 52 ft														

SYNTHETIC LANES



ITEM	Crosswise Tilts, Crowns, & Depressions +/- 0.030" at installation +/- 0.040" annually	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	Lane No.	
20 Synthetic Panel 1	Crosswise Tilt:	7 10	0	7 10	0	7 10	---	7 10	---	7 10	---	7 10	---	
	*Lengthwise Tilt:	F P	---	F P	---	F P	---	F P	---	F P	---	F P	---	
	Crowns (+) & Depressions (-)	Right 10 board:	+	32	-	15								
		Center 20 board:	+	31	-	25								
		Left 10 board:	+	36	-	10								
Distance:	4 ft													
21 Synthetic Panel 2	Crosswise Tilt:	7 10	0	7 10	0	7 10	---	7 10	---	7 10	---	7 10	---	
	*Lengthwise Tilt:	F P	---	F P	---	F P	---	F P	---	F P	---	F P	---	
	Crowns (+) & Depressions (-)	Right 10 board:	+	12	+	2								
		Center 20 board:	0		-	12								
		Left 10 board:	+	5	+	5								
Distance:	16 ft													
22 Synthetic Panel 3	Crosswise Tilt:	7 10	0	7 10	20	7 10	---	7 10	0	7 10	---	7 10	---	
	*Lengthwise Tilt:	F P	---	F P	---	F P	---	F P	---	F P	---	F P	---	
	Crowns (+) & Depressions (-)	Right 10 board:	-	9	-	13								
		Center 20 board:	-	18	+	18								
		Left 10 board:	-	8	+	7								
Distance:	28 ft													
23 Synthetic Panel 4	Crosswise Tilt:	7 10	0	7 10	20	7 10	---	7 10	---	7 10	---	7 10	---	
	*Lengthwise Tilt:	F P	---	F P	---	F P	---	F P	---	F P	---	F P	---	
	Crowns (+) & Depressions (-)	Right 10 board:	-	3	-	26								
		Center 20 board:	-	3	-	25								
		Left 10 board:	+	3	-	16								
Distance:	40 ft													
24 Synthetic Panel 5	Crosswise Tilt:	7 10	0	7 10	20	7 10	---	7 10	---	7 10	---	7 10	---	
	*Lengthwise Tilt:	F P	---	F P	---	F P	---	F P	---	F P	---	F P	---	
	Crowns (+) & Depressions (-)	Right 15 board:	+	14	+	11								
		Left 15 board:	+	9	-	17								
	Distance:	52 ft												

Completed copies are to be given to:

- Local Association Manager
(must be kept for 2 years)
- Center Representative
- USBC Headquarters

E-mail:
certifications@bowl.com

Mail:
USBC Headquarters
621 Six Flags Dr
Arlington, TX, 76011
ATTN: Center Inspection Coordinator

WITHIN 10 DAYS OF INSPECTION.

Upon submission, this center shall be placed on pending status. Once it has been verified this center meets USBC specifications, it will become certified for the current bowling season and a certificate will be delivered to the center's mailing address on record. Should an additional inspection be required, see Center Re-Inspection Report on BOWL.com.

REPORT AUTHORIZATION

We, the undersigned, representing the listed bowling association, have measured and inspected the physical specifications of the lanes referred to in this report and certify the measurements listed herein to be accurate.

Lead Inspector: Print: Donnell Johnson Sign: _____ Date: _____

Association Manager: Print: Courtney Tripp Sign: _____ Date: _____

I hereby acknowledge receipt of this report, and apply for USBC Center Certification.

Center Representative: Print: _____ Sign: _____ Date: _____