

SECTION A: ANNUAL SPECIFICATIONS



INSTRUCTIONS:

- ITEMS 1 THROUGH 8 AND SECTION C ARE TO BE INSPECTED ANNUALLY.
- FOR TILT MEASUREMENTS CIRCLE WHICH SIDE OF THE LEVEL THE FEELER GAUGES WERE PLACED UNDER.
 - 7 FOR 7 PIN SIDE, 10 FOR 10 PIN SIDE, P FOR PIN DECK SIDE, F FOR FOUL LINE SIDE
- COPY PAGE BEFORE INSPECTION FOR CENTERS WITH MORE THAN 12 LANES.

NOTE: IT IS RECOMMENDED THAT A LANE DRESSING INSPECTION REPORT BE SENT TO USBC BY SEPTEMBER 15TH.

ITEM	MEASUREMENT	DESCRIPTION	ALL LANES COMPLY?		FAILING LANE NUMBERS
1	AUTOMATIC FOUL DEVICES	Light remains on for 10 to 15 seconds and triggers no more than ¼" beyond of the approach side of the foul line.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
2	LANE PANEL DROP-OFFS	Drop off from trailing to leading edge. Specification: 0.000 – 0.040"	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
3	EDGE STRIPS	(FIBRE OR SYNTHETIC) Specification: Edge strips must be intact with a smooth, curved edge.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	
4	PIN SPOTTING	Specification: All pins must stand within their respective pin spots.	Yes: <input checked="" type="checkbox"/>	No: <input type="checkbox"/>	

				Lane No.											
				25	26	27	28	29	30	31	32	---	---	---	---
5	Kickback Plate to Kickback Plate (at rear row of pins)			59 3/4	59 7/8	59 5/8	59 3/4	59 11/16	59 3/4	59 11/16	59 3/4				
	Spec Range:	59 5/8"	60"												
6	Crosswise Tilt (at rear row of pins)			⁷ / ₁₀											
	Spec Range:	-0.040"	0.040"	0	0	0	0	0	0	010	0				
7	Lengthwise Tilt		Between 4-7 pins	^F / _P											
	Spec Range:	-0.187"	0.187"	050	095	020	020	050	010	050	010				
8	Gutter Depth (at rear row of pins)			7 pin	3 1/2	3 3/8	3 5/8	3 1/2	3 3/8	3 1/2	3 3/8	3 1/2			
	Spec Range:	3 3/8"	3 5/8"	10 pin	3 1/2	3 3/8	3 1/2	3 3/8	3 3/8	3 1/2	3 1/2	3 5/8			